


CS 6334 Virtual Reality Professor Yu Xiang The University of Texas at Dallas

Review of VR Systems






Figure by Dale Pond

10	/27/	/2021
	,	

- Sound corresponds to vibration in a medium
 - Air, water, solids
 - No sound in vacuum
- Pressure variation
 - Compression extreme to a decompressed, rarefaction extreme
- Sound waves are typically produced by vibrating solid materials
 - Striking a large bell
 - Air flow: flute
 - Humans: lungs to force air through the vocal cords

• Sound pressure level is reported in decibels (dB)

$$N_{db} = 20 * \log_{10}(p_e/p_r)$$
Pressure level of the peak compression
Reference pressure level
$$2 \times 10^{-7} \text{ newtons / square meter}$$


Breathing: 10 dB Conversion in restaurants: 60 dB Motorcycle at ft: 90 dB Jet take-off at 25 meters: 150 dB


10/27/2021

- Sound ray
 - Perpendicular to the sound propagation wavefront
- Wavelength Journey time Wave speed Distance traveled


- Attenuation
 - Sound intensity decreases by a constant factor (fixed percentage) for every unit distance from the source (exponential decay)
- Propagation speed
 - 343.2 meters per second through air at 20° C (68 ° F)
 - Light is about 874,000 times faster

- Frequency
 - The number of compressions per second (called pitch)
 - 20 Hz to 20,000 Hz for human hearing
 - Ultrasound: above 20,000 Hz
 - Infrasound: below 20 Hz
- Wavelength
 - At 20 Hz: $\lambda = 343.2/20 = 17.1 \text{m}$
 - At 20,000 Hz: $\lambda = 17.1 \mathrm{mm}$





Doppler Effect



Doppler Effect


 The received frequency shifts due to the relative motion between the source and the receiver

$$f_r = \begin{pmatrix} \frac{s + v_r}{s + v_s} \end{pmatrix} f_s \qquad \begin{array}{c} s = 343.2\\ v_r = -43.2\\ v_s = 0 \end{array}$$

- s is the propagation speed in the medium
- vr is the velocity of the receiver
- vs is the velocity of the source


Siren seems to change pitch as a policy car passed by

Reflection and Transmission



Reflection

Airborne sound transmission



Transmission

Diffraction






Figure 11.2: Waves can even bend around corners, due to *diffraction*. A top-down view of a room is shown. At each of the three interior corners, the propagating wavefront expands around it.




More diffraction occurs for longer wavelengths



10/27/2021


Spectral Decomposition



Fourier analysis: any periodic function can be decomposed into sinusoids


Directly adding the three pure tones

The Human Ear




- Pinna, amplifying sounds in 1500 Hz and 7500 Hz range
- Ear drum, 55mm², one pixel camera
- Middle ear (3 bones), converting vibrating air molecules in the outer ear into vibrating liquid in the inner ear
- Inner ear, the vestibular organs and the cochlea

The Cochlea



The Cochlea




Basilar membrane

- Thin and stiff near the base
- Soft and floppy near the apex

Spectral decomposition

Mechanoreceptors




A cross section of the organ of Corti. The basilar and tectorial membranes move relative to each other, causing the hairs in the mechanoreceptors to bend.

- Mechanoreceptors convert display of hairs into neural impulses
- Hairs are between the tectorial membrane and the basilar membrane
- Each ear contains around 20,000 mechanoreceptors (vs. 100 million photoreceptors in the eyes)

10/27/2021

Auditory Pathways



Primary auditory cortex

https://teachmeanatomy.info/neuroan atomy/pathways/auditory-pathway/

- Medial geniculate
- Inferior colliculus
- Superior olive
 - Cochlear nucleus

Auditory Perception


- Precedence effect
 - only one sound is perceived if two nearby identical sounds arrive at slightly different times





Right

Loudness Perception




Contours of equal loudness perception as a function of frequency

The **phon** is a logarithmic <u>unit</u> of <u>loudness</u> level for tones and complex sounds.


Pitch (Frequency) Perception

- Critical band masking
 - Block out waves that have frequencies outside of a particular range of interest
- Perception of differences in pitch
 - Just noticeable differences (JNDs)
 - < 1000Hz, JND 1Hz
 - 10,000Hz, JND 100Hz
- People perceive the tone of the fundamental frequency even when it is removed, and only higherorder harmonics remain
 - Fundamental frequency: largest amplitude wave



Localization

- Estimating the location of a sound source by hearing it (crucial for VR)
- Minimum Audible Angle (MAA): minimum amount of angular variation that can be detected by a human listener




Monaural Cues for Localization

- The pinna is shaped asymmetrically so that incoming sound is distorted in a way that depends on the direction from which it arrives, especially the elevation.
- The amplitude of a sound decreases quadratically with distance.
- For distant sounds, a distortion of the frequency spectrum occurs because higher-frequency components attenuate more quickly than lowfrequency components.
- The reverberations entering the ear as the sounds bounce around; this is especially strong in a room

Binaural Cues for Localization

 Interaural Level Difference (ILD), the difference in sound magnitude as heard by each ear

 Interaural Time Difference (ITD), the distance between the two ears is approximately 21.5cm, which results in different arrival times of the sound from a source



The cone of confusion is the set of locations where a point source might lie after using the ITD binaural cue.

Head Motion for Localization

- Auditory parallax, nearby audio sources change their azimuth and elevation faster than distant ones
- Integrating different cone of confusion for every head pose
- Doppler effect caused by the motion of a source relative to the receiver

Further Reading

• Section 11.1, 11.2 and 11.3, Virtual Reality, Steven LaValle