


Visual Rendering: Vertex Transforms

CS 6334 Virtual Reality

Professor Yu Xiang

The University of Texas at Dallas

Review of VR Systems




The Virtual World as 3D Triangle Meshes



Face-Vertex Meshes

Face List	Vertex List
f0	v0 v4 v5
f1	v0 v5 v1
f2	v1 v5 v6
f3	v1 v6 v2
f4	v2 v6 v7
f5	v2 v7 v3
f6	v3 v7 v4
f7	v3 v4 v0
f8	v8 v5 v4
f9	v8 v6 v5
f10	v8 v7 v6
f11	v8 v4 v7
f12	v9 v5 v4
f13	v9 v6 v5
f14	v9 v7 v6
f15	v9 v4 v7

example →



From Wikipedia


Visual Rendering

- Converting 3D scene descriptions into 2D images

- The graphics pipeline


- Geometry + transformations
- Cameras and viewing
- Lighting and shading
- Rasterization
- Texturing

From Computer Desktop Encyclopedia
Reprinted with permission.
© 1998 Intergraph Computer Systems




Primitives

- Vertex: 3D point $v(x, y, z)$
- Triangle (Face): 3D vertices
- Normal: 3D vector per vertex describing surface orientation $\mathbf{n} = (n_x, n_y, n_z)$




Vertex Transforms



https://www3.ntu.edu.sg/home/ehchua/programming/opengl/CG_BasicsTheory.html

Model Transform

- Transform each vertex from object coordinates to world coordinates
 - 3D rotation and 3D translation



Model Transform

- translation $T(d) = \begin{pmatrix} 1 & 0 & 0 & d_x \\ 0 & 1 & 0 & d_y \\ 0 & 0 & 1 & d_z \\ 0 & 0 & 0 & 1 \end{pmatrix}$

- scale $S(s) = \begin{pmatrix} s_x & 0 & 0 & 0 \\ 0 & s_y & 0 & 0 \\ 0 & 0 & s_z & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$

Vertex $\begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix}$

- rotation $R_z(\theta) = \begin{pmatrix} \cos\theta & -\sin\theta & 0 & 0 \\ \sin\theta & \cos\theta & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$


$R_x = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & \cos\theta & -\sin\theta & 0 \\ 0 & \sin\theta & \cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$

$R_y = \begin{pmatrix} \cos\theta & 0 & \sin\theta & 0 \\ 0 & 1 & 0 & 0 \\ -\sin\theta & 0 & \cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$

View Transform

- Transformation from world coordinate to camera or view coordinates

$$\mathbf{X}_{\text{cam}} = R\mathbf{X} + \mathbf{t} \quad \begin{bmatrix} R & \mathbf{t} \\ 0 & 1 \end{bmatrix} \quad 4 \times 4$$




View Transform

- Another way to specify the camera

- eye position $eye = \begin{pmatrix} eye_x \\ eye_y \\ eye_z \end{pmatrix}$

- reference position $center = \begin{pmatrix} center_x \\ center_y \\ center_z \end{pmatrix}$ Look at

- up vector $up = \begin{pmatrix} up_x \\ up_y \\ up_z \end{pmatrix}$




View Transform

- Compute 3 vectors

$$z^c = \frac{eye - center}{\|eye - center\|}$$

$$x^c = \frac{up \times z^c}{\|up \times z^c\|}$$

$$y^c = z^c \times x^c$$




View Transform

- Translation into eye position followed by rotation

$$M = R \cdot T(-e) = \begin{pmatrix} x_x^c & x_y^c & x_z^c & 0 \\ y_x^c & y_y^c & y_z^c & 0 \\ z_x^c & z_y^c & z_z^c & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} 1 & 0 & 0 & -eye_x \\ 0 & 1 & 0 & -eye_y \\ 0 & 0 & 1 & -eye_z \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

$$= \begin{pmatrix} x_x^c & x_y^c & x_z^c & -(x_x^c eye_x + x_y^c eye_y + x_z^c eye_z) \\ y_x^c & y_y^c & y_z^c & -(y_x^c eye_x + y_y^c eye_y + y_z^c eye_z) \\ z_x^c & z_y^c & z_z^c & -(z_x^c eye_x + z_y^c eye_y + z_z^c eye_z) \\ 0 & 0 & 0 & 1 \end{pmatrix}$$




$$z^c = \frac{eye - center}{\|eye - center\|}$$

$$x^c = \frac{up \times z^c}{\|up \times z^c\|}$$

$$y^c = z^c \times x^c$$


View Transform

- Most graphics APIs has a function called `lookat` to compute the view transform matrix
- In camera coordinates, the camera looks into negative z
- *Modelview matrix* is the combined model and view transformation matrix




Projection Transform

- Similar to choose lens and sensor of camera, specify field of view and aspect of camera
 - Perspective projection
 - Orthographic projection



Projection Transform: Perspective Projection

- View frustum in perspective view (four parameters)
 - Fovy: total vertical angle of view in degrees
 - Aspect: ratio of width/height
 - zNear: near clipping plane
 - zFar: far clipping plane



Perspective Projection: The camera's view frustum is specified via 4 view parameters: fovy, aspect, zNear and zFar.


Projection Transform: Perspective Projection

- Clipping-Volume Cuboid 2x2x2


$$f = \cot(\text{fovy} / 2)$$

$$M_{proj} = \begin{pmatrix} \frac{f}{aspect} & 0 & 0 & 0 \\ 0 & f & 0 & 0 \\ 0 & 0 & -\frac{zFar + zNear}{zFar - zNear} & -\frac{2 \cdot zFar \cdot zNear}{zFar - zNear} \\ 0 & 0 & 0 & -1 \end{pmatrix}$$

Flip z




Mapping



Projection Transform: Perspective Projection

- Specify the view frustum by left (l), right (r), bottom (b), and top (t) corner coordinates on near clipping plane (at zNear)


$$M_{proj} = \begin{pmatrix} \frac{2 \cdot zNear}{r-l} & 0 & \frac{r+l}{r-l} & 0 \\ 0 & \frac{2 \cdot zNear}{t-b} & \frac{t+b}{t-b} & 0 \\ 0 & 0 & -\frac{zFar + zNear}{zFar - zNear} & -\frac{2 \cdot zFar \cdot zNear}{zFar - zNear} \\ 0 & 0 & -1 & 0 \end{pmatrix}$$




Projection Transform: Orthographic Projection

- Camera is placed very far away (parallel projection)

$$M_{proj} = \begin{pmatrix} \frac{2}{r-l} & 0 & 0 & -\frac{r+l}{r-l} \\ 0 & \frac{2}{t-b} & 0 & -\frac{t+b}{t-b} \\ 0 & 0 & \frac{-2}{f-n} & -\frac{f+n}{f-n} \\ 0 & 0 & 0 & 1 \end{pmatrix}$$



Orthographic Projection v.s. Perspective Projection



Modelview Projection Matrix

- Combine all the transformations

$$v_{clip} = M_{proj} \cdot M_{view} \cdot M_{model} \cdot v = M_{proj} \cdot M_{mv} \cdot v$$

Vertex in clip space

Projection matrix

Modelview matrix


Viewport Transform

- Normalized Device Coordinate (NDC)

$$v_{clip} = \begin{pmatrix} x_{clip} \\ y_{clip} \\ z_{clip} \\ w_{clip} \end{pmatrix} \longrightarrow v_{NDC} = \begin{pmatrix} x_{clip} / w_{clip} \\ y_{clip} / w_{clip} \\ z_{clip} / w_{clip} \\ 1 \end{pmatrix} \begin{matrix} \in (-1,1) \\ \in (-1,1) \\ \in (-1,1) \\ \end{matrix}$$

vertex in clip space

vertex in NDC



Viewport Transform

- Define window as viewpoint ($x, y, \text{width}, \text{height}$)
 - (x, y) lower left corner of the viewport rectangle (default is $(0, 0)$)
 - Width, height size of viewport rectangle in pixels

$$v_{NDC} = \begin{pmatrix} x_{clip} / w_{clip} \\ y_{clip} / w_{clip} \\ z_{clip} / w_{clip} \\ 1 \end{pmatrix} \longrightarrow$$


vertex in NDC

$$v_{window} = \begin{pmatrix} x_{window} \\ y_{window} \\ z_{window} \\ 1 \end{pmatrix} \begin{matrix} \in (0, \text{width}) \\ \in (0, \text{height}) \\ \in (0, 1) \end{matrix}$$

vertex in window coords

$$\begin{aligned} x_{window} &= \frac{\text{width}}{2} (x_{NDC} + 1) + x \\ y_{window} &= \frac{\text{height}}{2} (y_{NDC} + 1) + y \\ z_{window} &= \frac{1}{2} z_{NDC} + \frac{1}{2} \end{aligned}$$

Vertex Transform Pipeline



Further Reading

- Section 3.4, 7.2, Virtual Reality, Steven LaValle

- 3D graphics with OpenGL, Basic Theory

https://www3.ntu.edu.sg/home/ehchua/programming/opengl/CG_BasicsTheory.html

- Textbook: Shirley and Marschner “Fundamentals of Computer Graphics”, AK Peters, 2009